

NEW

NEW





EXCLUSIVE CHARACTERISTICS

- INNOVATIVE GASKET
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- **▶ DETACHABLE TANK AND SOLID CART**
- MANUAL FILTER SHAKER
- **DOUBLE STAGE MOTORS**
- **BIG AND BRAKED WHEELS**
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE





GS 3/50 OPT

EXCLUSIVE CHARACTERISTICS

- INNOVATIVE GASKET
- **▶** INDEPENDENT MOTORS WITH LIGHT SWITCHES
- **▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE**
- **▶** DETACHABLE TANK AND SOLID CART
- MANUAL FILTER SHAKER
- **DOUBLE STAGE MOTORS**
- **BIG AND BRAKED WHEELS**
- > STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE

		GS 2/50 OPT	GS 3/50 OPT
Code		ASD015124	ASD015123
TECHNICAL DATA			
Usage		DRY	DRY
Number of phases		single phase	single phase
Voltage	V	220-240	220-240
N. and type of motor		2x2 stages	3x2 stages
Power	W	2000 - 2400 max	3000 - 3600 max
Water lift	mmH₂0	2470	2470
Airflow	m³/h	420	630
Tank Capacity	l	50	50
Diameter of inlet	mm	60	60
Filtering surface	cm²	12000 + 2260	12000 + 2260
Sound Pressure Level	dB(A)	74	76
Dimensions (LxWxH)	mm	580x700x1150	580x700x1150
Weight	Kg	64	66

STANDARD EQUIPMENT

CODE: FTDP88585
POLYESTER MAIN FILTER
12.000 CM²

CODE: FTDP72142 CARTRIDGE FILTER 2260 CM²







OPTIONAL ACCESSORIES

Basic tool kit Ø38-60 mm	PMDT00325
Anti-Static tool kit Ø38-60 mm	PMDT00326
Basic tool kit Ø50-60 mm	PMDT00443
Anti-Static tool kit Ø50-60 mm	PMDT00436

IP Cleaning S.p.A.