VACUUM CLEANERS - INDUSTRIAL SOLUTIONS - EXPOLOSION PROOF







PLANET 22S ATEX CE EX II 3D Ex to IIIB T200°C Do IP6X

EXCLUSIVE CHARACTERISTICS

- M & H FILTER CLASSIFICATION
- **TOTAL FILTRATION**
- Þ H CERTIFICATION
- **ESD COMPLIANCE**
- MULTI STAGE FILTRATION Þ
- **DOUBLE STAGE MOTORS AND TURBINE**
- **BIG AND BRAKED WHEELS** •
- NEW CONCEPT PROTECTIONS FOR INTERNAL ZONE 20
- **EXPLOSION PROOF TURBINE AND DESIGN FOR ATEX ZONE 22**

- **CONDUCTIVE WHEELS WITH BRAKES**
- STATIC DISSIPATING FILTERS
- CONDUCTIVE POLY LINER BAGS WITH SAFETY STRING
- PCB PREFILTER & ADDITIONAL CARTRIDGE
- COMPLIANCE WITH CLASS H CERTIFICATION
- HEPA H13 CARTRIDGE AND FILTERS SURFACE AREA
- FILTER OVERPRESSURE INDICATORS
- SAFETY DISPOSAL SYSTEMS
- ▶ RESITANT FRAMEWORK AND INLET PLUG FOR SAFE TRANSFER

PLANET 22S ATEX

Code	ASID00566
ΤΕCΗΝΙCΑΙ ΠΑΤΑ	

Usage		DRY
Motor		1
Power	W	1000-1200 max
Voltage	V	220-240
Water lift	mmH₂O	2470
Airflow	m³/h	210
Tank Capacity/Material	l	30/steel 430
Cable length	m	10
Sound Pressure Level	dB(A)	72
Diameter of inlet	mm	60
Diameter of accessories	mm	38/32
Dimensions (LxWxH)	mm	500x500x980
Weight	Kg	30

STANDARD EQUIPMENT

CODE: FTDP00618 **CONDUCTIVE MAIN FILTER**

CODE: FTDP00400 HEPA CARTRIDGE UPSTREAM

CODE: FTDP00610 HEPA CARTRIDGE PROTECTION

CODE: FTDP00399 **HEPA CARTRIDGE**



CODE: KTRI04687 CONDUCTIVE POLYLINER













OPTIONAL ACCESSORIES

Conductive tool kit Ø38/32 mm PMDT00015 High Reach Cleaning ATEX