



GC 1/35 OIL

EXCLUSIVE FEATURES

- ▶ INNOVATIVE GASKET
- ▶ DFS - DUAL FILTRATION SYSTEM FOR SIMULTANEOUS DRY AND WET PICK UP
- ▶ METAL INLET
- ▶ DOUBLE STAGE MOTOR
- ▶ STRONG HOOKS
- ▶ SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DRAIN VALVE

		GC 1/35 OIL
Code		ASD013709
TECHNICAL DATA		
Usage		WET & DRY
Number of phases		single phase
Voltage / Frequency	V	220-240/50-60
N. and type of motor		1 x 2 stages
Power	W	1000 - 1200 max
Water lift	mmH ₂ O	2470
Airflow	m ³ /h	210
Tank Capacity	l	35
Diameter of inlet	mm	60
Filtering surface	cm ²	2750
Sound Pressure Level	dB(A)	72
Dimensions (LxWxH)	mm	380x380x660
Weight	Kg	12,5

STANDARD EQUIPMENT

CODE: FTDP44002
POLYESTER CARTRIDGE
2.750 cm²



CODE: FTDP28755
MESH FILTER



CODE: PMVR02618
FASTENING PLASTIC RING



CODE: TBFX01318
CONDUCTIVE PU FLEXI-
BLE HOSE 3 m Ø38 mm



CODE: MPVR00152
PLASTIC TUBE 50 cm
(MACHINE COMES WITH
2 PCS)



CODE: LAFN28240
DOUBLE STEEL WAND
Ø38 mm



CODE: SPPV00156
FLAT LANCE Ø38 mm



CODE: SPPV43052
ROUND BRUSH Ø38 mm



CODE: SPPV01217
BRUSH Ø38 mm WITH
INTERCHANGEABLE
SLIDES

