



GS 2/50 FM OPT OIL

EXCLUSIVE FEATURES

- ▶ MODERN INDUSTRIAL DESIGN
- ▶ FLOWMIX SYSTEM TO ACTIVATE DOUBLE VACUUM SUCTION
- ▶ BIG RUBBER WHEELS WITH BREAKERS, EASY TO MOVE IN LARGE AREAS
- ▶ SIEVE BASKET TO SEPARATE ABRASIVE/CUTTING SOLIDS MIXED WITH LIQUIDS
- ▶ 2 HIGH VELOCITY MOTORS WITH TOP PERFORMANCES
- ▶ BEST SEALING OF THE POWERHEAD THANKS TO EXCLUSIVE BUILT-IN GASKET
- ▶ VISUAL FILLING INDICATOR AND DRAIN VALVE
- ▶ METAL TANGENTIAL INLET SEALED TO CREATE CYCLONIC EFFECT AND AVOID LEAKAGES

		GS 2/50 FM OPT OIL
Code		ASD013655
TECHNICAL DATA		
Usage		WET & DRY
Number of phases		single phase
Voltage / Frequency		V 220-240/50-60
N. and type of motor		2 x single stage HV
Power		W 2200 - 2600 max
Water lift		mmH ₂ O 2380 FM OFF / 3800 FM ON
Airflow		m ³ /h 400 FM OFF / 220 FM ON
Tank Capacity		l 50
Diameter of inlet		mm 60
Filtering surface		cm ² 2960
Sound Pressure Level		dB(A) 72
Dimensions (LxWxH)		mm 580x700x1150
Weight		Kg 45

STANDARD EQUIPMENT

CODE: MPVR10591
INTERNAL RING



CODE: FTDP00285
WASHABLE POLYESTER
CARTRIDGE 2.960 cm²



CODE: SECC00187
BUCKET SIEVE 30 L



CODE: FTDP28755
MESH FILTER



CODE: MPVR28723
FIXING SYSTEM FOR
MESH FILTER AND
CARTRIDGE



OPTIONAL ACCESSORIES

Complete multipurpose premium tool kit 3 m ø38 mm	PMDT01227
Complete multipurpose premium tool kit 4 m ø50 mm	PMDT01228
Complete Oil&Abrasives Tool kit 4 m ø38 mm	PMDT00928
Anti-oil tool kit for inlet ø60 mm	PMDT00447